

# 6080 B8 Multi-light

Universal HP lightweight putty-bodyfiller

**silco**<sup>®</sup>

Universal lightweight polyester putty with low specific weight.

- / Light weight 1.27 kg/L
- / Non-porous, smooth surface
- / Excellent sanding, beginning with P120
- / Very easy to spread
- / Excellent adhesion on various substrates



# 6080 B8 Multi-Light

Universal HP lightweight putty-bodyfiller

## Drying time\*

Dry to sand 20°C / 68 F	15–20 min
Potlife 20°C / 68 F	3–4 min

\*Indicative times subject to amount of hardener/application/environment.

## How to use?

Treated surface must be clean, dry, rust-free and grease-free. Optimal adhesion can be achieved on well abraded surface. For aluminium and galvanized steel, use matting pad+matting paste to improve adhesion. Mix the putty and hardener thoroughly until the colour is even. Use filler knife, plastic or rubber spatula for the application. Do not overdose! Excessive quantity of hardener can cause colour change on the topcoat and shorten the potlife. Hardener quantities below 2% can result in prolonged drying time.

For further and updated information please refer to the TDS published on [www.silco.si](http://www.silco.si).

## Packaging

Putty & Hardener

Prod. Nr.	Content	Color
6080-1,5	1.5 L	Beige
6080-CT-1,65	1.65 L	Beige
BPO Hardener 2–3 %	50 g, 60 g, 70 g	Red paste

## Product info

Universal lightweight polyester putty with low specific weight enables to fill irregularities and dents with significantly less product (by weight) in comparison to conventional putties. Excellent adhesion to galvanized and electrozinc-coated metals, aluminium and steel surfaces.